



MÖJJ ENGINEERING SYSTEMS LTD.

DRYERS

Excellence Through Innovation

EXPERIENCE

Over 36 Years of Drying Experience



Over **I500** Dryer Installations Worldwide

SPRAY DRYERS
FLUID BED DRYERS
FLASH DRYERS
AGITATED FLASH DRYERS
ROTARY DRYERS
CONDUCTION DRYERS
AGITATED THIN FILM DRYERS
VACCUM DRYERS

FRONTRUNNER IN SPRAY DRYERS

SPRAY DRYERS

This is a single step drying operation in which liquid feed solutions, emulsions, dispersions or slurries are directly converted to free flowing powder or granules.

Spray Dryers are custom designed to achieve product characteristics. Proper atomization methods and air flow patterns are selected to achieve this.



ROTARY DISC ATOMIZATION

A high speed rotating disc is used for atomizing the liquid feed. The disc throws the liquid outward or tangentially at high velocities forming fine droplets / mist. Instant drying takes place in contact with hot air forming free flowing dry powder.


Discs designs include straight / curved vanes, pin wheels, multilayer discs in diameters of 60mm, 100mm, 160mm, 250mm & 350mm for different capacities.

For high temperature applications special bearing cooling arrangements are provided.















FRONTRUNNER IN SPRAY DRYERS

NOZZLE ATOMIZATION

Feed Solution or Slurry at high pressure is atomized through a nozzle into fine droplets and then dried instantaneously. Various types of air flow patterns are possible with nozzle atomization systems. Nozzle type spray dryers are used to produce material in the granular, non-dusty form or powder form as required.

Depending on the desired physical properties of end product, the choice of co-current, counter current or mixed air flow is selected.




SINGLE-FLUID NOZZLE,



CO-CURRENT MODE



TWO-FLUID NOZZLE, **FOUNTAIN MODE**



FEATURES

- Wide range of materials can be dried.
- Options of both single fluid / two fluid nozzles.
- Easy to operate and user friendly.
- Compact layout.
- Automatic / Remote nozzle change over with steam / air flushing.
- PLC / DCS
- CIP
- Explosion proof designs





CUSTOMIZED DRYING

FLUIDISED SPRAY DRYERS CUM GRANULATORS

Spray Dryers with Integrated Fluid Beds are ideally used to meet special particle size, dispersibility and bulk density requirements. The spray comes in contact with fluidized dried particles and agglomerates. External fluidized bed systems are provided for finish drying, de-dusting, and product cooling.



INTEGRATED FLUID BED DRYER

APPLICATIONS

- Suitable for production of granular, non dusting, instantised or hygroscopic products.
- Plant evaporation capacities from 100 Kg / hr onwards.
- Design available for explosive / hazardous products.
- Energy efficient operation







EXTERNAL FLUID BED DRYER





CLOSED LOOP SPRAY DRYERS

When the product to be dried is oxidisable or laden with flammable / explosive solvents, nitrogen purged closed loop systems are preferred. These are typically used in Pharma Industry.

ADVANTAGES

- Ideal for solvent laden, flammable / explosive product to be dried.
- Inert gas drying avoids oxidising of material.
- Recovery of costly solvents
- Special nitrogen purged atomizers to achieve desired product particle size and bulk density.
- Solvent recovery of upto 98.5%

RELIABLE TECHNOLOGY IN CONDUCTION DRYERS

CONDUCTION DRYERS

This range of dryers employ the conduction mode of drying. These dryers ensure low temperature gentle drying of the product. Conduction dryers are designed taking into consideration the wet and dry product flow characteristics, lump crust formation tendency and thermal sensitivity. These could be indirect with tubes or jacket.



INDIRECT STEAM TUBE ROTARY DRYER

Indirect Steam Tube Rotary Dryer comprises of tubes fixed to a rotating shell. Steam passes through the tubes. The wet material present in the rotary shell is lifted by means of lifters and showered. The product is dried by means of the indirect contact with steam. The entire shell is supported on rollers and rotated by means of tyres & girth gear.

A Sealing arrangement is provided to avoid air leakage and product losses.

ADVANTAGES

Rugged construction | Continuous operation | Gentle drying of material Thermally efficient | Low operating & maintenance cost

ROTARY TUBE BUNDLE DRYERS

A Tube Bundle is like a heat exchanger, rotated in a stationary insulated housing. Lifters provided on the tube bundle lift the material and shower them on the hot tube bundle surface. Steam is passed from one end of Tube Bundle for drying and condensate is removed from the other end

ADVANTAGES

- Gentle drying.
- No breaking of material.
- High heat economy.
- Continuous operation.



REVOLUTIONARY ROTARY DRYERS

ROTARY DRYERS

Rotary Dryers are work horses. They are rugged and robust in which the solids to be dried are showered in a hot stream of air and dried during travel through the dryer.







DIRECT ROTARY DRYER

Direct Rotary Dryer comprises of a rotating inclined shell through which a hot stream of air flows. The wet material present in the rotary shell is lifted by means of spiral flights and showered in hot flowing air. Due to this direct contact, the product is dried.

Rotary Dryers are available with co-current or counter current air flow patterns depending on the properties of individual products to be dried.

The internals are designed to ensure uniform distribution over the entire cross section.

The entire shell is supported on rollers and rotated by means of tyres and girth gear or by means of a friction drive. Sealing arrangement is also provided so as to have a minimum air leakage and product loss.

DIRECT ROTARY COOLERS

Direct Rotary Coolers are used for cooling product to the desired temperature before packing. The product is showered in an air stream by internal lifters. Amblent de-humidified air is used for cooling.

ADVANTAGES

Ideally suited for large capacity application and uneven particle size distributionContinuous operation and versatile application | Low operating & maintenance cost.

STATE-OF-THE-ART FLUID BED DRYERS

FLUID BED DRYERS CUM COOLERS

Fluid bed dryers are offered for free flowing granular powders. These are static equipment having benefits of high Heat Transfer coefficient. Cooling is possible just by extension of the Fluid Bed.



VIBRATORY FLUID BED DRYERS

Vibratory Fluid bed dryers are used for granular / crystaline powders which are difficult to fluidize. Air fluidization is supplemented by mechanical vibrations to achieve uniform bed distribution on the perforated plate.

The dryer offers better control on fluidisation, residence time, product moisture and dust levels.

Explosion proof designs



CLOSED LOOP FLUID BED DRYERS


- Inertised drying of free floowing Agro chemical cake with ethyl acetate solvent.
- Reduces risk of oxidization of product.



ADVANTAGES

Adjustable residence times to suit each individual product | Uniform product temperature possible Drying and cooling in a single step

WINNING TECHNOLOGY IN FLASH DRYERS



FLASH DRYERS

Flash Dryers are used for drying wet cakes, crystals or granular products. These are long ducts carrying air at a high velocity and the material is dried while it is pneumatically conveyed along with hot air.

ADVANTAGES

- Continuous operation & single step drying of free flowing powders, crystals.
- Unique feeding devices for taking case of uneven feed moistures.
- Less floor space.

CAGE MILL FLASH DRYERS

For materials where size reduction is desired along with drying Flash dryers with Cage Mills are ideally suited. Materials in the nature of lumps, semi-hardcakes can easily be dried.



AGITATED FLASH DRYERS

Are used when the material to be dried is sticky in nature, thixotropic and requires longer drying time.

Closed Loop design with inert gas for solvent recovery.

ADVANTAGES

Continuous operation & single step drying | Disintegration of dry hard product lumps or crusts

Particle size control | Recycling of hot gases

VACCUM DRYERS

VACCUM DRYERS

Vaccum dryers are used to facilitate rapid and low temperature drying of heat sensitive products without raising their temperature.

ROTARY VACUUM DRYERS/COOLERS

These Dryers are horizontal cylindrical jacketed chambers and are equipped with a central shaft to which paddles or ribbons and scrappers can be attached for agitation and mixing.

Vacuum in drying chamber allows drying of material at low temperature.

For recovery of solvent condensors and receivers are provided.

ADVANTAGES

- Low temperature agitated vacuum drying
- Ideal for heat sensitive products which can be agitated.
- Minimum space required.
- Recovery of Solvent

ADVANTAGES

- Low temperature gentle drying.
- Ideal for heat sensitive products.
- Minimum space required.
- Solvent Recovery





AIR BROOM

Air broom is made of pipe having multiple nozzles. This broom pipe is rotating inside the Drying Chamber at low rpm through gear box and motor.

Dehumidified air is passing through the pipe for air brooming through nozzles to remove the deposition from chamber shell.

CLEANING IN PLACE

CLEANING IN PLACE (CIP)

Cleaning in Place, as a packaged system, can be added on to the Drying system where frequent cleaning of dryer chamber or the complete plant is required. Cleaning can be with manual or automatic sequential operation.

ADVANTAGES

Quick product changeover | Economical use of wash water | Uniform and consistent washing













SAFETY

Drying Systems are also offered incorporating special safety features like Pressure / Vacuum relief device, Rupture Vents, Fire Fighting features, Explosion Isolation Barriers etc.

Depending on the product characteristics and operating conditions of the dryer, the system components can be custom designed to withstand the permissible over-pressure requirements.

CONTROLS & INSTRUMENTATION








The performance, safety and efficiency of a drying system depends upon accurate monitoring & control of the operating parameters and control logic.

Manual / semi-automatic or fully automatic control modes can be incorporated - Microprocessor based single loop feedback / cascade controls; Programmable Logic Control (PLC) with man machine interface / Personal computer or Distributed Control system (DCS) interface to match the client's control philosophy.



RESEARCH AND DEVELOPMENT

R & D Center recognized by Dept. of Sciences & Technology, Govt. of India houses facilities for laboratory testing of materials on Pilot plants.

THE LABORATORY HOUSES PILOT PLANTS FOR

Spray Dryer | Agitated Flash Dryer | Fluid Bed Dryer | Integrated Fluidised Bed Spray Dryer
Air De-humidification unit | Automated Controls & Instrumentation








Agitated Flash Dryer
[Options of various designs of
Attritors]



Agitated Thin Film Dryer

Image Analysis of Spray Dried Products Comparison of Samples



Mojj pilot plant sample analysis




External Lab sample analysis

Laboratory testing on material is conducted by well trained & dedicated professionals to establish characteristics and generate data for sizing. scale up & repeatability. The above services are offered to customers.

ACCOLADES

Recognition for us, in the field of dryers, has come by way of the prestigious Parkhe Award instituted by the chamber of Commerce for innovative design, development and commercialization of the Combination Spray Dryer.



ARENA OF SITE ACTIVITIES





- Large dryers can be built / assembled at site from shop fabricated components.
- Trained / skilled technical fabrication professionals.
- Experience of erection at various locations and altitudes.
- Timely completion using advanced modern tools.







USER INDUSTRIES

CHEMICAL PROCESS INDUSTRIES

Aluminium hydroxide Sodium Sulphate Aluminium Flouride Organic Metals Formaldehyde Resins Organic Metals Fine Chemicals **Wood Preservatives** Polymer Emulsions Potassium Flouride Ligno Sulphonates Dicalcium Phosphate Managenese Sulphate Mangenese Corbonate Polystyerene Beads **Metal Salts** Vinyl Polymer Vinyl Sulphone

FOOD STUFF

Whole / Skimmed Milk
Fruit Pulp & Juices
Tea and Coffee Extract
Lactose
Whole Egg Powder
Chilli
Instant coffee powder
Cheese
Cassein
Food Colours / Flavours
Cereals
Salts

Proteins

DYESTUFF & AUXILLARIES

Reactive Dyes
Dispersing Agents
Acid Dyes
Direct Dyes
Organic Pigments
Detergents
Tinopal
Disperse Dyes
Inorganic Pigments
Optical Brightner
Leather Chemicals
Basic Chromium Sulphate
Sodium Lauryl Sulphates
Olefin Sulphonate

NATURAL PRODUCTS

Herbal Extracts
Yeast
Hydrolised Protein
Alovera
Spirulina Algae
Enzymes
Cellulose
Acetates
Animal Feed / Waste

PHARMACEUTICAL

Pharma Base
Bulk Drugs
Manitol USP
Applied Pharma Ingredient
Pharma Intermediates
Clinical Dextran
Sodium-2-Ethyl Hexonate

CARBOHYDRATES

Starch

Gum

Maize / Wheat

Gluten

Wheat Flour

Soya Flour

Sorbitol

Maltodextrine

Glucose / Dextrose

PESTICIDES, FUNGICIDES, HERBICIDES

Sulphur Derivatives

Mancozeb

Urea Formldehyde

Melamine Formaldehyde

CERAMICS & MINERALS

Kaolin

Silica

Enamels

Sand

Coal

Limestone

Ferrites |

Zirconium Silicate

Metal Oxides

Tableware

Activated Earths

Mica

Alumina

Tile Slip

Insulators

Technical Ceramics

Mojj Philosophy

We belive and recognize the basic fact that each customer has his own specific and not so specific needs to be catered to, requirements to be met and problems to be solved. We therefore strive in giving our services suited to these specific and peculiar needs of our customer. This calls for understanding these needs and transferring them into an engineering solution. No aspect of a plant is too minor to be ignored and no process requirement too complex to be met.

Range of Products

Dryers

- Spray
- Fluid Bed
- Flash
- Rotary
- Conduction

Evaporators

- Falling Film
- Forced Circulation
- Scraped Surface
- Wiped Film
- Natural Circulation

Bio-Technology

- Fermentation and Distillation
- Composting
- Pre-Clarifiers

Mixers

- Top Entry
- Side Entry
- Blenders
- Blungers

Turnkey plants

- Non Diary Creamer
- Powder Milk
- Starch
- Detergents

Pollution Control

- Flue Gas Spray Scrubber
- Wet Scrubber
- Incinerators
- Bag Filters
- Thermal oxidiser through Anguil USA



MOJJ Engineering Systems Ltd.

81-B /15, M. I. D. C. Bhosari, Pune - 411 026 (India). Tel: + 91-20-27120360 / 27122837.

Email

dryer@mojjpune.com | evaporator@mojjpune.com | distillery@mojjpune.com

Website

www.mojjpune.com

Branch offices At

New Delhi | Ahmedabad | Bangalore | Chennai

Works (India)

Unit I: Bhosari, Pune | Unit II: Ranjangaon, Pune | Unit III: Markal (Alandi), Pune | Unit IV: Vatva, Ahmedabad